

LK Electronic room control M60

LK Minishunt M60 can be equipped with wired or wireless room control. The shunt's capillary tube connected room thermostat is then replaced with a LK Actuator. The table below shows a summary of the required items.

There are three wired systems, S1, S2 Basic and ICS-W. For more information, see Product range - Room control.



Wired room control S1 Basic

Article no.	Article name	Color	Number	Pack.
241 72 87	LK Room Thermostat S1 Basic, 24V NO	White polished, RAL 9010	1 st	1/50
241 73 28	LK Connection Box 1, 24V	-	1 st	1/60
241 77 47	LK Transformer 230/24 V AC	-	1 st	1/12
241 75 91	LK Actuator 24V NO	-	1 st	1/100/1800



Wired room control S2 Basic

Article no.	Article name	Color	Number	Pack.
243 43 99	LK Room Thermostat S2 Basic, 24V NO	Back white 9003.Front white/ice gray	1 st	1/25
241 73 28	LK Connection Box 1, 24V	-	1 st	1/60
241 77 47	LK Transformer 230/24 V AC	-	1 st	1/12
241 75 91	LK Actuator 24V NO	-	1 st	1/100/1800

Wired room control ICS-W

Article no.	Article name	Color	Number	Pack.
241 73 08	LK Thermostat ICS-W	White, high gloss*	1 st	1/25
241 73 11	LK Receiver ICS-W1	-	1 st	1/10
241 75 91	LK Actuator 24V NO	-	1 st	1/100/1800

**Also available in high gloss black and silver grey.*



Wireless room control ICS-RF

Article no.	Article name	Color	Number	Pack.
241 73 02	LK Thermostat ICS-RF	White, high gloss*	1 st	1/25
241 73 05	LK Receiver ICS-RF1	-	1 st	1/10
241 75 91	LK Actuator 24V NO	-	1 st	1/100/1800

** Also available in high gloss black and silver grey.*