

LK Cabinet Stand

DESCRIPTION


LK Cabinet stand is intended for temporary fixing of LK Manifold Cabinet UFH, LK Shunt Cabinet UFH and LK Manifold Cabinet UNI. The stand is used for preassembly of cabinets for under floor heating/potable water systems over insulation prior to concrete pour.

The cabinet stand consists of two steel poles, four pipe clips with bolts and 2 x 300 mm long sleeves. The sleeves prevent the stand legs from being set in concrete, allowing the stand to be reused.

ASSEMBLY




Mounted cabinet stand.



Close up on attachment to cabinet.


Assemble 4 x M8 bolts to threaded nuts in the back of the cabinet (cabinets are fitted with fixed threaded holes). Thread the pipe clips to protruding bolts on the back of the cabinet. Attach the legs and slip on the sleeves. The sleeves prevent the legs being set into the concrete and thereby make the stand reusable. Hammer the legs through the insulation and into the sand base, until the installation is firm and stable. Set the cabinet to a suitable height and tighten the clamps.

Tape the sleeves to the legs of the stand to prevent them from floating up during concrete pouring.



LK Cabinet Stand with LK Manifold Cabinet

LK FOOT FOR MANIFOLD/CABINET STAND



LK Foot for Manifold/Cabinet stand is available as accessory to facilitate installation on for example an existing concrete slab.

ORDER INFORMATION

Article	Article no.
LK Cabinet Stand, H 1750 mm	241 88 94

ACCESSORIES

Article	Article no.
LK Foot for Manifold/Cabinet stand (pair) W 30 x L 200 x H 95 mm	241 91 08
LK Sleeve dim 25	187 06 65